



ATS 601

100% SATIN POLYESTER

- Printable 1 side (outside)
- Cost efficient
- Uncoated

Satin Polyester is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The calendaring of **ATS 601** allows it to be printed on the outside.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

Printable 1 side only

Printable both sides

POLYESTER

- **ATP 811** ○
Dyeing process resistant

- **ATP 812** ○
Dyeing process resistant
- **ATP 802** ●

SATIN

- **ATS 821** ○ ●
Anti-Fray
- **ATS 811** ○
Dyeing/Tanning/Stonewashing...
- **ATS 601** ○ ●

- **ATS 612** ○ ●
 Recycled yarns
- **ATS 602** ○ ●

NYLON

- **ATN 501** ○
Anti-Fray

- **ATN 802** ○
Roll up resistant
- **ATN 602** ○

Resistances

Washing
AATCC61-2A

Ironing

Stone washing

Tanning

Enzyme washing

Dry cleaning

Dyeing process

Anti-fray

Roll specifications

- **Core diameter:** 1", 1,5", 2", 3"
- **Roll width:** min 20 mm, max 220 mm
- **Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information

Certifications

- REACH / SVHC 1907/2006/EC

• **STANDARD 100**
CQ 1172/3
IFTH

Fabric specifications

- **Color:** white, black
- **Density:**
 - Warp: 120 yarns/cm
 - Weft: 41 yarns/cm
- **Total weight: 106 g/m²**
 - Fabric weight 106 g/m²
 - This fabric is uncoated
- **Thickness:** < 0,110mm



Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)