



ATP 811

- Printable 1 side (outside)
- Smooth touch & tear resistant
- Dyeing process resistant
- Coated one side

Polyester Taffeta is a polyester fiber based fabric. This material gives excellent resistance to harsh mechanical manipulation (tearing, scratching...), a smooth and supple surface which brings comfort in case of skin contact. The coating allows it to be printable with Thermal Transfer technology and resist to the dyeing process and stone washing.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

100% POLYESTER taffeta

Printable 1 side only

Printable both sides

POLYESTER

- **ATP 811** ○
Dyeing process resistant

- **ATP 812** ○
Dyeing process resistant
- **ATP 802** ●

SATIN

- **ATS 821** ○ ●
Anti-Fray
- **ATS 811** ○
Dyeing/Tanning/Stonewashing...
- **ATS 601** ○ ●

- **ATS 612** ○ ●
 Recycled yarns
- **ATS 602** ○ ●

NYLON

- **ATN 501** ○
Anti-Fray

- **ATN 802** ○
Roll up resistant
- **ATN 602** ○

Resistances

- | | |
|------------------------------------|---------------------|
| Washing
Domestic 80-85°C | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Roll specifications


- **Core diameter:** 1", 1,5", 2", 3"
 - **Roll width:** min 20 mm, max 220 mm
 - **Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information*

Certifications

- REACH / SVHC 1907/2006/EC
- **STANDARD 100**
CQ 1172/3
IFTH

Fabric specifications

- **Color:** white
- **Density:**
 - Warp: 42 yarns/cm
 - Weft: 31 yarns/cm
- **Total weight: 92 g/m²**
 - Coating weight 30 g/m²
 - Fabric weight 62 g/m²
- **Thickness:** < 0,165mm



Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)