



ATS 612

- Printable both sides
- Recycled yarns
- Uncoated

Satin Polyester is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. **ATS 612** is made of recycled yarns.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

100% SATIN POLYESTER

Printable 1 side only

Printable both sides

POLYESTER

• **ATP 811** ○
Dyeing process resistant

• **ATP 812** ○
Dyeing process resistant

• **ATP 802** ●

SATIN

• **ATS 821** ○ ●
Anti-Fray

• **ATS 811** ○
Dyeing/Tanning/Stonewashing...

• **ATS 612** ○ ●
Recycled yarns

• **ATS 601** ○ ●

• **ATS 602** ○ ●

NYLON

• **ATN 501** ○
Anti-Fray

• **ATN 802** ○
Roll up resistant

• **ATN 602** ○

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Roll specifications

- **Core diameter:** 1", 1.5", 2", 3"
 - **Roll width:** min 20 mm, max 220 mm
 - **Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information

Certifications

- REACH / SVHC 1907/2006/EC



STANDARD
100
CQ 1172/4
IFTH



Certification pending

Fabric specifications

- **Color:** white, black
- **Density:**
 - Warp: 118 yarns/cm
 - Weft: 38 yarns/cm
- **Total weight: 140 g/m²**
 - Fabric weight 140 g/m²
 - This fabric is uncoated
- **Thickness:** < 0,135mm
- **Recycled yarns**



Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)