



ATS 821

100% SATIN POLYESTER

- Printable 1 side (outside)
- Anti-fray
- Coated one side

Satin Polyester is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The coating of **ATS 821** allows it to resist to fraying.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

Printable 1 side only

Printable both sides

POLYESTER

- **ATP 811** Dyeing process resistant

- **ATP 812** Dyeing process resistant
- **ATP 802**

SATIN

- **ATS 821** Anti-Fray
- **ATS 811** Dyeing/Tanning/Stonewashing...
- **ATS 601**

- **ATS 612** Recycled yarns
- **ATS 602**

NYLON

- **ATN 501** Anti-Fray

- **ATN 802** Roll up resistant
- **ATN 602**

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Roll specifications

- **Core diameter:** 1", 1,5", 2", 3"
 - **Roll width:** min 20 mm, max 220 mm
 - **Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information

Certifications

- REACH / SVHC 1907/2006/EC
- **STANDARD 100**
CQ 1172/3 IFTH

Fabric specifications

- **Color:** white, black
- **Density:**
 - Warp: 120 yarns/cm
 - Weft: 41 yarns/cm
- **Total weight: 109 g/m²**
 - Coating weight 4 g/m²
 - Fabric weight 105 g/m²
- **Thickness:** < 0,125mm



Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)