



ATN 501

- Printable 1 side (outside)
- Cost efficient
- Coated both sides

ATN 501 provides highly accurate printing at a competitive price level compared to other printable fabric materials. The coating is formulated to make this material printable with Thermal Transfer technology on the outside.


Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Fabric specifications

- Color:** white
- Density:**
 - Warp: 46 yarns/cm
 - Weft: 21 yarns/cm
- Total weight: 65 g/m²**
 - Coating weight 34 g/m²
 - Fabric weight 31 g/m²
- Thickness:** < 0,130mm



NYLON taffeta

Printable 1 side only

Printable both sides

POLYESTER

• **ATP 811** ○
Dyeing process resistant

• **ATP 812** ○
Dyeing process resistant

• **ATP 802** ●

SATIN

• **ATS 821** ○ ●
Anti-Fray

• **ATS 811** ○
Dyeing/Tanning/Stonewashing...

• **ATS 612** ○ ●
Recycled yarns

• **ATS 601** ○ ●

• **ATS 602** ○ ●

NYLON

• **ATN 501** ○
Anti-Fray

• **ATN 802** ○
Roll up resistant

• **ATN 602** ○

Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
- Roll width:** min 20 mm, max 220 mm
- Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information

Certifications

- REACH / SVHC 1907/2006/EC

Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)