



ATN 802

- Printable both sides
- Roll up resistant after washing
- Coated both sides

ATN 802 provides highly accurate printing at a competitive price level compared to other printable fabrics materials. The coating allows it to be printable using Thermal Transfer technology and remain flat after washing cycles.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

NYLON/POLYESTER blend taffeta

Printable 1 side only

Printable both sides

POLYESTER

• **ATP 811** ○
Dyeing process resistant

• **ATP 812** ○
Dyeing process resistant

• **ATP 802** ●

SATIN

• **ATS 821** ○ ●
Anti-Fray

• **ATS 811** ○
Dyeing/Tanning/Stonewashing...

• **ATS 612** ○ ●
Recycled yarns

• **ATS 601** ○ ●

• **ATS 602** ○ ●

NYLON

• **ATN 501** ○
Anti-Fray

• **ATN 802** ○
Roll up resistant

• **ATN 602** ○

Resistances

Washing
AATCC61-2A

Ironing

Stone washing

Tanning

Enzyme washing

Dry cleaning

Dyeing process

Anti-fray

Roll specifications

- **Core diameter:** 1", 1,5", 2", 3"
- **Roll width:** min 20 mm, max 220 mm
- **Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information


Certifications

- REACH / SVHC 1907/2006/EC

• **STANDARD 100**
CQ 1172/3
IFTH

Fabric specifications

- **Color:** white
- **Density:**
 - Warp: 43 yarns/cm
 - Weft: 22 yarns/cm
- **Total weight: 70 g/m²**
 - Coating weight 16 g/m²
 - Fabric weight 54 g/m²
- **Thickness:** < 0,125mm



Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)