



## ATN 802

- Printable both sides
- Roll up resistant after washing
- Coated both sides

**ATN 802** provides highly accurate printing at a competitive price level compared to other printable fabrics materials. The coating allows it to be printable using Thermal Transfer technology and remain flat after washing cycles.


Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

### Resistances

- |                              |                     |
|------------------------------|---------------------|
| <b>Washing</b><br>AATCC61-2A | <b>Ironing</b>      |
| Stone washing                | Tanning             |
| Enzyme washing               | <b>Dry cleaning</b> |
| Dyeing process               | Anti-fray           |

### Fabric specifications

- Color:** white
- Density:**
  - Warp: 43 yarns/cm
  - Weft: 22 yarns/cm
- Total weight: 70 g/m<sup>2</sup>**
  - Coating weight 16 g/m<sup>2</sup>
  - Fabric weight 54 g/m<sup>2</sup>
- Thickness:** < 0,125mm



## NYLON taffeta

Printable 1 side only

Printable both sides

### POLYESTER

• **ATP 811** ○  
Dyeing process resistant

• **ATP 812** ○  
Dyeing process resistant

• **ATP 802** ●

### SATIN

• **ATS 821** ○ ●  
Anti-Fray

• **ATS 811** ○  
Dyeing/Tanning/Stonewashing...

• **ATS 612** ○ ●  
Recycled yarns

• **ATS 601** ○ ●

• **ATS 602** ○ ●

### NYLON

• **ATN 501** ○  
Anti-Fray

• **ATN 802** ○  
Roll up resistant

• **ATN 602** ○

### Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
- Roll width:** min 20 mm, max 220 mm
- Roll length:** min 50 m, max 400 m

Refer to the offer brochure for more information

### Certifications

- REACH / SVHC 1907/2006/EC**



### Storage conditions

- Recommended:** 12 months
- Humidity rate:** 20-80%
- Temperature:** 5-35°C (40-95°F)