



ATS 811

- Printable 1 side (outside)
- Resistant to several industrial processes
- Coated both sides

Satin Polyester is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The coating of **ATS 811** allows it to resist to several garment/leather processes such as stone washing, enzyme washing, tanning, dyeing process and anti-fray.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

Resistances

- | | |
|------------------------------|---------------------|
| Washing
AATCC61-2A | Ironing |
| Stone washing | Tanning |
| Enzyme washing | Dry cleaning |
| Dyeing process | Anti-fray |

Fabric specifications

- Color:** white
- Density:**
 - Warp: 120 yarns/cm
 - Weft: 40 yarns/cm
- Total weight: 108 g/m²**
 - Coating weight 3 g/m²
 - Fabric weight 105 g/m²
- Thickness:** < 0,115mm



100% SATIN POLYESTER

Printable 1 side only	Printable both sides
POLYESTER	
<ul style="list-style-type: none"> • ATP 811 ○ Dyeing process resistant 	<ul style="list-style-type: none"> • ATP 812 ○ Dyeing process resistant • ATP 802 ●
SATIN	
<ul style="list-style-type: none"> • ATS 821 ○ ● Anti-Fray • ATS 811 ○ Dyeing/Tanning/Stonewashing... • ATS 601 ○ ● 	<ul style="list-style-type: none"> • ATS 612 ○ ● Recycled yarns • ATS 602 ○ ●
NYLON	
<ul style="list-style-type: none"> • ATN 501 ○ Anti-Fray 	<ul style="list-style-type: none"> • ATN 802 ○ Roll up resistant • ATN 602 ○

Roll specifications

- Core diameter:** 1", 1,5", 2", 3"
 - Roll width:** min 20 mm, max 220 mm
 - Roll length:** min 50 m, max 400 m
- Refer to the offer brochure for more information

Certifications

- REACH / SVHC 1907/2006/EC
- **STANDARD 100**
CQ 1172/3 IFTH

Storage conditions

- **Recommended:** 12 months
- **Humidity rate:** 20-80%
- **Temperature:** 5-35°C (40-95°F)