



## ATS 811

- Printable 1 side (outside)
- Resistant to several industrial processes
- Coated both sides

**Satin Polyester** is a polyester fiber based fabric. The polyester fibers give the material an excellent resistance to tearing and the satin weaving allows it to have a soft and comfortable look and feel. The coating of **ATS 811** allows it to resist to several garment/leather processes such as stone washing, enzyme washing, tanning, dyeing process and anti-fray.

Selected for optimal compatibility with **ATX 1**, **ATX 7**, **ATX 9** Thermal Transfer Ribbon.

## 100% SATIN POLYESTER

Printable 1 side only

Printable both sides

### POLYESTER

• **ATP 811** ○  
Dyeing process resistant

• **ATP 812** ○  
Dyeing process resistant

• **ATP 802** ●

### SATIN

• **ATS 821** ○ ●  
Anti-Fray

• **ATS 811** ○  
Dyeing/Tanning/Stonewashing...

• **ATS 612** ○ ●  
Recycled yarns

• **ATS 601** ○ ●

• **ATS 602** ○ ●

### NYLON

• **ATN 501** ○  
Anti-Fray

• **ATN 802** ○  
Roll up resistant

• **ATN 602** ○

### Resistances



**Washing**  
AATCC61-2A



**Ironing**



**Stone washing**



**Tanning**



**Enzyme washing**



**Dry cleaning**



**Dyeing process**



**Anti-fray**

### Roll specifications

- Core diameter: 1", 1,5", 2", 3"
- Roll width: min 20 mm, max 220 mm
- Roll length: min 50 m, max 400 m

Refer to the offer brochure for more information

### Certifications

- REACH / SVHC 1907/2006/EC



### Fabric specifications

- Color: white
- Density:
  - Warp: 120 yarns/cm
  - Weft: 40 yarns/cm
- Total weight: **108 g/m<sup>2</sup>**
  - Coating weight 3 g/m<sup>2</sup>
  - Fabric weight 105 g/m<sup>2</sup>
- Thickness: < 0,115mm



### Storage conditions

- Recommended: 12 months
- Humidity rate: 20-80%
- Temperature: 5-35°C (40-95°F)